



SATIN CAST BLACK / SMOKE

RIPROCK 24	24"
Stack (mm)	449
Reach (mm)	350
Lunghezza Tubo Sterzo (mm)	95
Angolo Sterzo (°)	68
Altezza movimento centrale (mm)	287.5
B-B Drop (mm)	30
Trail (mm)	83
Lunghezza Forcella (mm)	370
Offset Forcella/Rake (mm)	42
Avancorsa (mm)	565
Lunghezza Batticatena (mm)	390
Interasse (mm)	953
Lunghezza Tubo Orizz. virtuale (mm)	479
Altezza Standover (mm)	593
Lunghezza piantone (mm)	310
Angolo Sella (°)	73.5
Lunghezza Pedivella (mm)	140
Larghezza Manubrio (mm)	620
Lunghezza attacco manubrio (mm)	35
Larghezza sella (mm)	130
Lunghezza reggisella (mm)	300

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	A1 Premium Butted Alloy, unisex frame, internal cable routing, 148mm thru-axle, 30.9mm dropper post ready, replaceable derailleur hanger compatible
FORCELLA	A1 Premium Butted Alloy, Alloy steerer, 15x110 mm, W/Mini Fender
ATTACCO MANUBRIO	3D Forged Aluminum, 35mm length, 6-degree rise, 31.8mm clamp diameter
MANUBRIO	Mini Rise, Alloy Double Butted, 9-degree Backsweep, 620mm Width, 31.8mm
MANOPOLE	Specialized Trail Grips, lock-on
FRENO ANT.	C-STAR Hydraulic Disc Brake, 160mm rotor, adjustable reach
FRENO POST.	C-STAR Hydraulic Disc Brake, 160mm rotor, adjustable reach
CAMBIO POST.	microSHIFT Advent RD-M6195M, 9-speed, w/ clutch
COMANDI	microSHIFT Advent SL-M9295, 9-speed
CASSETTA	microSHIFT Advent, 9-speed, 11-42t
CATENA	KMC X9EPT, Anti-corrosion coating, Missing Link™
GUARNITURA	Forged Alloy, 140mm length, narrow Q-factor, w/ chainguard
INGRANAGGI	Alloy 30T, narrow-wide design
MOVIM. CENTR.	Square-tapered, 68mm
PEDALI	Nylon platform w/ reflectors
CERCHI	Alloy, 16mm depth, 25mm internal width, 28H
MOZZO ANT.	Alloy, 6-Bolt, 28H, 15x110 Boost
MOZZO POST.	Alloy, 6-Bolt, 28H, 12x148 Boost, 11-speed compatible
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Ground Control Sport, 24x2.35"
PNEUMATICO POST.	Ground Control Sport, 24x2.35"
CAMERE	Presta, 32mm valve
SELLA	Kids Bridge Saddle, 130mm
REGGISELLA	Alloy, 0mm offset, 2-bolt clamp, 30.9mm, 300mm length
COLLARINO	Bolt-type, 34.9mm

ART. NR.	DESCRIZIONE	COLORE	MISURA
96522-8711	RIPROCK 24 INT	SATIN CAST BLACK / SMOKE	24



GLOSS FLO RED / BLACK

SPECIFICHE TECNICHE	Specialized si riserva il diritto di modificare le caratteristiche senza preavviso.
TELAIO	A1 Premium Butted Alloy, unisex frame, internal cable routing, 148mm thru-axle, 30.9mm dropper post ready, replaceable derailleur hanger compatible
FORCELLA	A1 Premium Butted Alloy, Alloy steerer, 15x110 mm, W/Mini Fender
ATTACCO MANUBRIO	3D Forged Aluminum, 35mm length, 6-degree rise, 31.8mm clamp diameter
MANUBRIO	Mini Rise, Alloy Double Butted, 6-degree Backsweep, 600mm Width, 31.8mm, 19mm Bar End Diameter
MANOPOLE	Specialized Trail Grips, 19mm bar end diameter, lock-on
FRENO ANT.	C-STAR Hydraulic Disc Brake, 160mm rotor, adjustable reach
FRENO POST.	C-STAR Hydraulic Disc Brake, 160mm rotor, adjustable reach
CAMBIO POST.	microSHIFT Advent RD-M6195M, 9-speed, w/ clutch
COMANDI	microSHIFT Advent SL-M9295, 9-speed
CASSETTA	microSHIFT Advent, 9-speed, 11-42t
CATENA	KMC X9EPT, Anti-corrosion coating, Missing Link™
GUARNITURA	Forged Alloy, 115mm length, narrow Q-factor, w/ chainguard
INGRANAGGI	Alloy 30T, narrow-wide design
MOVIM. CENTR.	Square-tapered, 68mm
PEDALI	Nylon platform w/ reflectors
CERCHI	Alloy, 16mm depth, 25mm internal width, 28H
MOZZO ANT.	Alloy, 6-Bolt, 28H, 15x110 Boost
MOZZO POST.	Alloy, 6-Bolt, 28H, 12x148 Boost, 11-speed compatible
RAGGI	Stainless, 14g
PNEUMATICO ANT.	Ground Control Sport, 20x2.35"
PNEUMATICO POST.	Ground Control Sport, 20x2.35"
CAMERE	Schrader valve
SELLA	Kids Bridge Saddle, 130mm
REGGISSELLA	Alloy, 0mm offset, 2-bolt clamp, 30.9mm, 300mm length
COLLARINO	Bolt-type, 34.9mm

RIPROCK 20	20"
Stack (mm)	385
Reach (mm)	295
Lunghezza Tubo Sterzo (mm)	75
Angolo Sterzo (°)	68
Altezza movimento centrale (mm)	239
B-B Drop (mm)	30
Trail (mm)	66
Lunghezza Forcella (mm)	320
Offset Forcella/Rake (mm)	40
Avancorsa (mm)	482
Lunghezza Batticatena (mm)	350
Interasse (mm)	830
Lunghezza Tubo Orizz. virtuale (mm)	405
Altezza Standover (mm)	520
Lunghezza piantone (mm)	290
Angolo Sella (°)	73.5
Lunghezza Pedivella (mm)	115
Larghezza Manubrio (mm)	600
Lunghezza attacco manubrio (mm)	35
Larghezza sella (mm)	130
Lunghezza reggisella (mm)	300

ART. NR.	DESCRIZIONE	COLORE	MISURA
96522-8009	RIPROCK 20 INT	GLOSS FLO RED / BLACK	20